

SL-BS64-8 Shifting Lever

For proper and safe performance, read and follow these instructions carefully.

The SL-BS64-8 is exclusively designed for Shimano 600 Ultegra 8-speed system.
Use in combination with the rear derailleur RD-6401.


Note

- For Shimano Index System (SIS) use in combination with the following components.
 - Shifting lever SL-BS64-8
 - Rear derailleur RD-6401
 - Freehub FH-6402-HG
 - Cassette sprocket CS-HG90-8
 - Chain CN-HG90
 - Outer cable Shimano SIS-SP sealed cable
 - Inner cable Shimano ϕ 1.2mm inner cable
- For SIS use, the wire efficiency for an inner cable routed internal through the handle bar is not good, and so it cannot be used.
- The SL-BS64-8 can be installed to a handle bar with an inner diameter of from 19 to 22mm.
- For optimum performance use shorter handle bar.

Lever installation

(The illustration shows the example for installation of the lever for the rear to a drop handle bar, but the lever for the front is installed in the same manner.)


- 1** Set the body unit to the handle bar, and then tighten the body fixing bolt in the counterclockwise direction by using a 6mm hexagonal wrench.




- 2** Install the lever boss to the body unit.



- 3** Set so that the projection of the lever boss cover faces downward.




- 4** Align the SIS ▲ letters and the red ▼, and then set so that the grip part of the lever unit faces downward.




- 5** Tighten the lever fixing bolt by using a flat-tip screwdriver.



- 6** Install the cable stopper to the brazed-on boss.




- 7** With the cable placed along the handle bar, cover the cable with the outer cable guide, and use tape or similar material to provisionally attach to the handle bar.




- 8** Wrap the handle bar with bar tape.

SIS operation

Turn the ring to select either SIS or friction. Turn the ring until the red ▼ of the ring is correctly aligned with the SIS ▲ or FRIC ▼ mark.



After making a selection, be sure to fold the ring downward.



• Please note: Specifications are subject to change for improvement without notice. (English)

SHIMANO AMERICAN CORPORATION

One Holland Irvine CA 92618 U.S.A. Phone 949-951-5003

SHIMANO EUROPA

Industrieweg 24 NL-8071 CT Nunspeet Holland Phone 31-341-272222

SHIMANO INC.

77 Oimatsu-cho 3-cho Sakai Osaka 590-8577 Japan Phone 0722-23-3243